

CVC-1705

B/W Weatherproof Varifocal Bullet Camera



This 1/3" B/W CCD camera, which has a 4mm-9mm adjustable varifocal lens and electronic shutter is the best choice for adaptable focal settings. The weather-resistant housing is furnished with a protective sunshield and the cable is routed through the "conduit compatible" mounting bracket for extra protection.

Specifications

| | |
|-----------------------|---|
| Resolution | 420 line |
| Minimum Illumination | 0.02 lux |
| Image Device | 1/3" B/W CCD image sensor |
| Lens | 4-9mm adjustable varifocal |
| Electronic Shutter | 1/60 - 1/100000 seconds |
| Operating Temperature | 14 degrees F to 122 degrees F |
| Humidity | Within 95% RH |
| Scanning Frequency | 15.75 kHz horizontal 60 Hz vertical |
| Number of Pixels | 512 horizontal x 492 vertical |
| Video S/N Ratio | Greater than 46 dB |
| Video Output | 1.0 Vp-p 75 ohm |
| Output | Video-RCA with BNC adapter, power-DC jack |
| Power Supply | Regulated 12V DC power supply (UL and CSA listed) |
| Housing Color | Black, miniature weatherproof |
| Dimensions | 4.5"L x 2"W x 2"H |
| Weight | 11.2 oz |

Specifications subject to change



For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880