



B/W Scanning Bullet Camera

(CVC-1760)

Our indoor bullet scanning camera packages allow for large area coverage. The CVC-1760 has an adjustable automatic rotation range from 10° - 270°, complete with a remote control. With 420 line resolution and the ability to see in low light conditions of 0.02 lux F 1.4, the camera can be used for night applications. This light weight camera unit includes a wall mount bracket, making for a quick and easy installation, and a 12V DC power supply. A color version of this

Features NEW multi-functional remote control for speed and scanning adjustments.

Technical Specifications

Base Dimensions	1 3/8" H x 2 3/8" Dia.
Speed	Auto 1/60 - 1/100000 seconds
Housing	black
Humidity	Within 95 % RH
Image Pick up Device	1/3" B/W CCD image sensor
Lens	3.6mm wide angle, 78 degree diagonal
Minimum Illumination	0.02 lux F 1.4
Mount	Wall mount bracket included
Number of Pixels	512 horizontal x 492 vertical
Temperature	14 degrees F- 122 degrees F
Outputs	Video-RCA with BNC adapter, power- DC jack
Overall Dimensions	4"L x 1.5"W x 5.25"H
Power Consumption	100 mA
Power Supply	listed)
Resolution	420 line
Scanning System	EIA standard 525 line 60 fields/second
Special	Remote control included adjusts speed & angle of scanning
Video Output Level	1.0 Vp-p 75 ohm
Video S/N RAtio	Greater than 46 dB